

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.:	25-1-SR	2K-PE-Feinspachtel SR	
Print date	09.02.2026	Revision date 28.08.2025	EN
Version	14.86	Issue date 28.08.2025	Page 1 / 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier):	25-1-SR
Trade name/designation	2K-PE-Feinspachtel SR weiß UFI: RX00-W08V-700E-A5HP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Putty

Uses advised against:

Aware of any other information

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

P.A. Jansen GmbH u. Co., KG Hochstadenstraße 22 D-53474 Bad Neuenahr-Ahrweiler	Telephone: +49 2641 3897-0 Homepage: www.jansen.de
--	--

Department responsible for information:

laboratory

E-mail (competent person) sicherheitsdatenblatt@jansen.de

1.4. Emergency telephone number

Emergency telephone number	+49 2641 3897-51
Only available during office hours.	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Repr. 2 / H361d	Reproductive toxicity	Suspected of damaging the unborn child.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe aerosol.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 25-1-SR 2K-PE-Feinspachtel SR
Print date 09.02.2026 Revision date 28.08.2025 EN
Version 14.86 Issue date 28.08.2025 Page 2 / 12

P264 Wash hands thoroughly after handling.
P280 Wear protective gloves and eye protection/face protection.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370 + P378.6 In case of fire: Use carbon dioxide, extinguishing powder or alcohol-resistant foam to extinguish.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard components for labelling

maleic anhydride
Styrene
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and
2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino] ethanol

Supplemental hazard information

No data available

2.3. **Other hazards**

No information available.

SECTION 3: Composition/information on ingredients

3.2. **Mixtures**

Description 2K-Polyester putty

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
202-851-5 100-42-5 601-026-00-0	01-2119457861-32 Styrene Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Repr. 2 H361d / STOT SE 3 H335 / STOT RE 1 H372 / Asp. Tox. 1 H304 / Aquatic Chronic 3 H412 / Flam. Liq. 3 H226 Acute toxicity estimate (ATE): ATE (inhalation, vapour): 11,80 mg/L	8 - 10
246-562-2 25013-15-4	01-2119622074-50 Vinyltoluene Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Asp. Tox. 1 H304 / Aquatic Acute 1 H400 / Aquatic Chronic 2 H411 / Flam. Liq. 3 H226	3 - 5
205-500-4 141-78-6 607-022-00-5 911-490-9	01-2119475103-46 Ethyl acetate Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066 01-2119979579-10 Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino] ethanol Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Skin Sens. 1 H317 / Aquatic Chronic 3 H412	1 - 1,5 0,5 - 1
203-571-6 108-31-6 607-096-00-9	01-2119472428-31 maleic anhydride Acute Tox. 4 H302 / STOT RE 1 H372 / Skin Corr. 1B H314 / Eye Dam. 1 H318 / Resp. Sens. 1 H334 / Skin Sens. 1A H317 / EUH071 Specific concentration limit (SCL): Skin Sens. 1A H317 >= 0,001 Acute toxicity estimate (ATE): ATE (oral): 1090 mg/kg bw	0,1 - 0,15

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. **Description of first aid measures**

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Article No.: 25-1-SR 2K-PE-Feinspachtel SR
Print date 09.02.2026 Revision date 28.08.2025
Version 14.86 Issue date 28.08.2025

EN
Page 3 / 12

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. **Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. **Advice for firefighters**

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. **Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. **Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. **Reference to other sections**

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. **Precautions for safe handling**

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 25-1-SR 2K-PE-Feinspachtel SR
Print date 09.02.2026 Revision date 28.08.2025
Version 14.86 Issue date 28.08.2025

EN
Page 4 / 12

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSivO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

Styrene

Index No. 601-026-00-0 / EC No. 202-851-5 / CAS No. 100-42-5

WEL, TWA: 430 mg/m³; 100 ppm

WEL, STEL: 1080 mg/m³; 250 ppm

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

WEL, TWA: 734 mg/m³; 200 ppm

WEL, STEL: 1468 mg/m³; 400 ppm

maleic anhydride

Index No. 607-096-00-9 / EC No. 203-571-6 / CAS No. 108-31-6

WEL, TWA: 1 mg/m³

WEL, STEL: 3 mg/m³

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

DNEL long-term dermal (systemic), Workers: 63 mg/kg

DNEL acute inhalative (local), Workers: 1468 mg/m³

DNEL acute inhalative (systemic), Workers: 1468 mg/m³

DNEL long-term inhalative (local), Workers: 734 mg/m³

DNEL long-term inhalative (systemic), Workers: 734 mg/m³

DNEL long-term oral (repeated), Consumer: 4,5 mg/kg

DNEL long-term dermal (systemic), Consumer: 37 mg/kg

DNEL acute inhalative (local), Consumer: 734 mg/m³

DNEL acute inhalative (systemic), Consumer: 734 mg/m³

DNEL long-term inhalative (local), Consumer: 367 mg/m³

DNEL long-term inhalative (systemic), Consumer: 367 mg/m³

maleic anhydride

Index No. 607-096-00-9 / EC No. 203-571-6 / CAS No. 108-31-6

DNEL acute dermal, short-term (local), Workers: 0,04 mg/kg

DNEL acute dermal, short-term (systemic), Workers: 0,04 mg/kg

DNEL long-term dermal (local), Workers: 0,04 mg/kg

DNEL long-term dermal (systemic), Workers: 0,04 mg/kg

DNEL acute inhalative (local), Workers: 0,8 mg/m³

DNEL acute inhalative (systemic), Workers: 0,8 mg/m³

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 25-1-SR 2K-PE-Feinspachtel SR
Print date 09.02.2026 Revision date 28.08.2025
Version 14.86 Issue date 28.08.2025

EN
Page 5 / 12

DNEL long-term inhalative (local), Workers: 0,4 mg/m³
DNEL long-term inhalative (systemic), Workers: 0,4 mg/m³

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7

DNEL long-term inhalative (local), Workers: 10 mg/m³
DNEL long-term oral (repeated), Consumer: 700 mg/kg

PNEC:

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

PNEC aquatic, freshwater: 0,24 mg/L
PNEC aquatic, marine water: 0,024 mg/L
PNEC aquatic, intermittent release: 1,65 mg/L
PNEC sediment, freshwater: 1,15 mg/kg
PNEC sediment, marine water: 0,115 mg/kg
PNEC, soil: 0,148 mg/kg
PNEC sewage treatment plant (STP): 650 mg/L
PNEC Secondary Poisoning: 200 mg/kg

maleic anhydride

Index No. 607-096-00-9 / EC No. 203-571-6 / CAS No. 108-31-6

PNEC aquatic, freshwater: 0,0428 mg/L
PNEC aquatic, marine water: 0,0043 mg/L
PNEC aquatic, intermittent release: 0,4281 mg/L
PNEC sediment, freshwater: 0,334 mg/kg
PNEC sediment, marine water: 0,0334 mg/kg
PNEC, soil: 0,0415 mg/kg
PNEC sewage treatment plant (STP): 44,6 mg/L

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7

PNEC aquatic, freshwater: 0,184 mg/L
PNEC aquatic, marine water: 0,0184 mg/L
PNEC aquatic, intermittent release: 0,193 mg/L
PNEC sediment, freshwater: 1000 mg/kg
PNEC sediment, marine water: 100 mg/kg
PNEC, soil: 100 mg/kg
PNEC sewage treatment plant (STP): 100 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits as specified by the manufacturer. Recommended respiratory protection articles: Inadequately ventilated workplaces and spraying procedures are necessary. Fresh air mask or short-time work combination filter A2-P2 are recommended.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 25-1-SR 2K-PE-Feinspachtel SR
Print date 09.02.2026 Revision date 28.08.2025
Version 14.86 Issue date 28.08.2025

EN
Page 6 / 12

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid
Colour:	white
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	-84 °C Source: Ethyl acetate
Initial boiling point and boiling range:	77 °C Source: Ethyl acetate
Flammability:	Flammable liquid and vapour.
Lower and upper explosion limit:	
Lower explosion limit:	1 Vol-% Method: literature value Source: Styrene
Upper explosion limit:	7,7 Vol-% Method: literature value Source: Styrene
Flash point:	31 °C Method: EN ISO 1523
Auto-ignition temperature:	490 °C Source: Styrene
Decomposition temperature:	No data available
pH at 20 °C:	No data available
Kinematic viscosity (40°C):	> 47592,39 mm²/s
Viscosity at 2 °C:	85000 mPa* s
Solubility(ies):	
Water solubility at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	714 mbar Source: Styrene
Density and/or relative density:	
Density at 20 °C:	1,79 g/cm³ Method: DIN 53217
Relative vapour density:	No data available
particle characteristics:	not applicable

9.2. Other information

Solid content:	85 weight-%
solvent content:	
Organic solvents:	15 weight-%
Water:	0 weight-%

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 25-1-SR 2K-PE-Feinspachtel SR
Print date 09.02.2026 Revision date 28.08.2025
Version 14.86 Issue date 28.08.2025

EN
Page 7 / 12

section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Styrene

oral, LD50, Rat: 5000 mg/kg

dermal, LD50, Rat: > 2000 mg/kg

inhalative (vapours), LC50, Rat: 11,8 mg/L (4 h)

Ethyl acetate

dermal, LD50, Rabbit: > 2000 mg/kg

inhalative (vapours), LC50, Rat: 29,3 mg/L (4 h)

inhalative (vapours), LC50, Rat: 22,5 mg/L (6 h)

oral, LD50, Rabbit: 4934 mg/kg

Method: OECD 401

maleic anhydride

oral, LD50, Rat: 1090 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: 2620 mg/kg

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 425

dermal, LD50, Rabbit: > 2000 mg/kg

inhalative (dust and mist), LC50, Rat: 3,43 - 5,09 mg/L (4 h)

Method: OECD 403

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye irritation.

Ethyl acetate

eyes

irritant.

maleic anhydride

Skin

Causes burns.

eyes

Causes burns.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

maleic anhydride

Skin:

Method: OECD 406

sensitising

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Suspected of damaging the unborn child.

STOT-single exposure; STOT-repeated exposure

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 25-1-SR 2K-PE-Feinspachtel SR
Print date 09.02.2026 Revision date 28.08.2025
Version 14.86 Issue date 28.08.2025

EN
Page 8 / 12

May cause damage to organs through prolonged or repeated exposure.

Ethyl acetate

Specific target organ toxicity (single exposure), drowsiness

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

Styrene

Fish toxicity, LC50, Pimephales promelas: 10 mg/L (96 h)

Ethyl acetate

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 230 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna: 610 mg/L (48 h)

Bacteria toxicity, EC10, Pseudomonas putida: 2900 mg/L (16 h)

Algae toxicity, EC50, Desmodesmus subspicatus: 5600 mg/L (72 h)

maleic anhydride

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 75 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 42,81 mg/L (48 h)

Method: OECD 202

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 74,35 mg/L (72 h)

Method: OECD 201

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 100 mg/L (96 h)

Daphnia toxicity, LC50, Daphnia magna: > 100 mg/L (48 h)

Algae toxicity, EC50, Pseudokirchneriella subcapitata: 16 mg/L (72 h)

Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

Ethyl acetate

Fish toxicity, NOEC, Pimephales promelas (fathead minnow): > 9,65 mg/L (32 d)

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 2,4 mg/L (21 d)

Method: OECD 211

Algae toxicity, NOEC, Desmodesmus subspicatus: > 100 mg/L (72 h)

Method: OECD 201

Bacteria toxicity, NOEC, Pseudomonas putida: 650 mg/L (16 h)

maleic anhydride

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 10 mg/L (21 d)

12.2. Persistence and degradability

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 25-1-SR 2K-PE-Feinspachtel SR
Print date 09.02.2026 Revision date 28.08.2025
Version 14.86 Issue date 28.08.2025

EN
Page 9 / 12

Ethyl acetate
Biodegradation: > 70 % (20 d); Evaluation Readily biodegradable (according to OECD criteria)
Method: OECD 301D / EEC 92/69 annex V, C.4-E

maleic anhydride
Biodegradation: Evaluation Readily biodegradable (according to OECD criteria)
Method: OECD 301B

12.3. Bioaccumulative potential

Ethyl acetate
Partition coefficient: n-octanol/water: 0,68

maleic anhydride
Partition coefficient: n-octanol/water: -2,61
Method: OECD 107

Bioconcentration factor (BCF)

Ethyl acetate
Bioconcentration factor (BCF): 30

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]
Bioconcentration factor (BCF), Oncorhynchus mykiss (Rainbow trout): 19 - 352

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number or ID number

UN 3269

14.2. UN proper shipping name

Land transport (ADR/RID): Polyester resin kit liquid base material
Sea transport (IMDG): POLYESTER RESIN KIT liquid base material
Air transport (ICAO-TI / IATA-DGR): Polyester resin kit liquid base material

14.3. Transport hazard class(es)

3
for packages ≤ 450 litres Transport in accordance with 2.3.2.5 of the IMDG Code.

14.4. Packing group

III

14.5. Environmental hazards

Land transport (ADR/RID) No data available

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 25-1-SR 2K-PE-Feinspachtel SR
Print date 09.02.2026 Revision date 28.08.2025
Version 14.86 Issue date 28.08.2025

EN
Page 10 / 12

Marine pollutant No data available

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Category: P5c FLAMMABLE LIQUIDS

Quantity 1: 5000 t / Quantity 2: 50000 t

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. B/b) ; VOC limit value: 250 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 250

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
202-851-5 100-42-5	Styrene	01-2119457861-32
246-562-2 25013-15-4	Vinyltoluene	01-2119622074-50
205-500-4 141-78-6	Ethyl acetate	01-2119475103-46
911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino] ethanol	01-2119979579-10
203-571-6 108-31-6	maleic anhydride	01-2119472428-31

SECTION 16: Other information

Full text of classification in section 3:

Acute Tox. 4 / H332

Acute toxicity (inhalative)

Harmful if inhaled.

Skin Irrit. 2 / H315

Skin corrosion/irritation

Causes skin irritation.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

Repr. 2 / H361d

Reproductive toxicity

Suspected of damaging the unborn child.

STOT SE 3 / H335

STOT-single exposure

May cause respiratory irritation.

STOT RE 1 / H372

STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

Asp. Tox. 1 / H304

Aspiration hazard

May be fatal if swallowed and enters airways.

Aquatic Chronic 3 / H412

Hazardous to the aquatic environment

Harmful to aquatic life with long lasting effects.

Flam. Liq. 3 / H226

Flammable liquids

Flammable liquid and vapour.

Aquatic Acute 1 / H400

Hazardous to the aquatic environment

Very toxic to aquatic organisms.

Aquatic Chronic 2 / H411

Hazardous to the aquatic environment

Toxic to aquatic life with long lasting effects.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 25-1-SR 2K-PE-Feinspachtel SR
 Print date 09.02.2026 Revision date 28.08.2025
 Version 14.86 Issue date 28.08.2025

EN
 Page 11 / 12

Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
STOT RE 1 / H372	STOT-repeated exposure	Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Skin Corr. 1B / H314	Skin corrosion/irritation	Causes severe skin burns and eye damage.
Resp. Sens. 1 / H334	Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1A / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3	Flammable liquids	On basis of test data.
Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.
Repr. 2	Reproductive toxicity	Calculation method.
STOT RE 2	STOT-repeated exposure	Calculation method.
Aquatic Chronic 3	Hazardous to the aquatic environment	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MAK	Maximum workplace concentration
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Data sources

Data arise from reference works and literature.

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.:	25-1-SR	2K-PE-Feinspachtel SR
Print date	09.02.2026	Revision date 28.08.2025
Version	14.86	Issue date 28.08.2025

EN
Page 12 / 12

EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.