

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 22-3 Ahrweitex- Schnellspachtel
Print date 09.02.2026 Revision date 28.08.2025 EN
Version 25.7 Issue date 28.08.2025 Page 1 / 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier): 22-3
Trade name/designation Ahrweitex- Schnellspachtel
weiss

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

P.A. Jansen GmbH u. Co., KG
Hochstadenstraße 22 Telephone: +49 2641 3897-0
D-53474 Bad Neuenahr-Ahrweiler
Homepage: www.jansen.de

Department responsible for information:

laboratory
E-mail (competent person) sicherheitsdatenblatt@jansen.de

1.4. Emergency telephone number

Emergency telephone number +49 2641 3897-51
Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

Hazard statements

No data available

Precautionary statements

No data available

Hazard components for labelling

No data available

Supplemental hazard information

EUH210 Safety data sheet available on request.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Spatula on styrene alkyd base

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No.	REACH No.	weight-%
CAS No.	Designation	
Index No.	classification: // Remark	
215-535-7	01-2119488216-32	
1330-20-7	Xylene	5 - 7
601-022-00-9	Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / STOT SE 3 H335 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Flam. Liq. 3 H226	

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.:	22-3	Ahrweitex- Schnellspachtel	
Print date	09.02.2026	Revision date 28.08.2025	EN
Version	25.7	Issue date 28.08.2025	Page 2 / 11

919-857-5	01-2119463258-33 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / STOT SE 3 H336 / EUH066	3 - 5
202-849-4	01-2119489370-35	
100-41-4	Ethylbenzene	2 - 2,5
601-023-00-4	Acute Tox. 4 H332 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Aquatic Chronic 3 H412 / Flam. Liq. 2 H225	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 22-3 Ahrweitex- Schnellspachtel
Print date 09.02.2026 Revision date 28.08.2025
Version 25.7 Issue date 28.08.2025

EN
Page 3 / 11

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

Barium sulfate

EC No. 231-784-4 / CAS No. 7727-43-7

WEL, TWA: 10 mg/m³

Remark: (inhalable fraction)

WEL, TWA: 4 mg/m³

Remark: (respirable fraction)

Talc (Mg₃H₂(SiO₃)₄)

EC No. 238-877-9 / CAS No. 14807-96-6

WEL, TWA: 1 mg/m³

Remark: (respirable fraction)

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m³; 50 ppm

WEL, STEL: 441 mg/m³; 100 ppm

Remark: (may be absorbed through the skin)

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

Ethylbenzene

Index No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

WEL, TWA: 441 mg/m³; 100 ppm

WEL, STEL: 552 mg/m³; 125 ppm

Remark: (may be absorbed through the skin)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 22-3 Ahrweitex- Schnellspachtel
Print date 09.02.2026 Revision date 28.08.2025
Version 25.7 Issue date 28.08.2025

EN
Page 4 / 11

Additional information

TWA : Long-term occupational exposure limit value
STEL : short-term occupational exposure limit value
Ceiling : peak limitation

DNEL:

Ethylbenzene

Index No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

DNEL long-term dermal (systemic), Workers: 180 mg/kg
DNEL long-term inhalative (local), Workers: 293 mg/m³
DNEL long-term inhalative (systemic), Workers: 77 mg/m³
DNEL long-term inhalative (local), Workers: 293 mg/m³
DNEL long-term oral (repeated), Consumer: 1,6 mg/kg
DNEL acute inhalative (systemic), Consumer: 15 mg/m³

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

DNEL long-term dermal (systemic), Workers: 212 mg/kg
DNEL acute inhalative (local), Workers: 442 mg/m³
DNEL acute inhalative (systemic), Workers: 442 mg/m³
DNEL long-term inhalative (local), Workers: 221 mg/m³
DNEL long-term inhalative (systemic), Workers: 221 mg/m³
DNEL long-term oral (repeated), Consumer: 12,5 mg/kg
DNEL long-term dermal (systemic), Consumer: 125 mg/kg
DNEL acute inhalative (local), Consumer: 260 mg/m³
DNEL acute inhalative (systemic), Consumer: 260 mg/m³
DNEL long-term inhalative (local), Consumer: 65,3 mg/m³
DNEL long-term inhalative (systemic), Consumer: 65,3 mg/m³

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

EC No. 919-857-5

DNEL long-term dermal (systemic), Workers: 300 mg/kg
DNEL long-term inhalative (systemic), Workers: 1500 mg/m³
DNEL long-term oral (repeated), Consumer: 300 mg/kg
DNEL long-term dermal (systemic), Consumer: 300 mg/kg
DNEL long-term inhalative (systemic), Consumer: 900 mg/m³

Barium sulfate

EC No. 231-784-4 / CAS No. 7727-43-7

DNEL long-term oral (repeated), Workers: 10 mg/kg
DNEL long-term inhalative (local), Workers: 10 mg/m³
DNEL long-term inhalative (systemic), Workers: 10 mg/m³
DNEL long-term oral (repeated), Consumer: 13000 mg/kg
DNEL long-term inhalative (systemic), Consumer: 10 mg/m³

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7

DNEL long-term inhalative (local), Workers: 10 mg/m³
DNEL long-term oral (repeated), Consumer: 700 mg/kg

PNEC:

Ethylbenzene

Index No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

PNEC aquatic, freshwater: 0,1 mg/L
PNEC aquatic, marine water: 0,01 mg/L
PNEC aquatic, intermittent release: 0,1 mg/L
PNEC sediment, freshwater: 13,7 mg/kg
PNEC sediment, marine water: 1,37 mg/kg
PNEC, soil: 2,68 mg/kg
PNEC sewage treatment plant (STP): 9,6 mg/L
PNEC Secondary Poisoning: 20 mg/kg

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

PNEC aquatic, freshwater: 0,327 mg/L

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 22-3 Ahrweitex- Schnellspachtel
Print date 09.02.2026 Revision date 28.08.2025
Version 25.7 Issue date 28.08.2025

EN
Page 5 / 11

PNEC aquatic, marine water: 0,327 mg/L
PNEC aquatic, intermittent release: 0,327 mg/L
PNEC sediment, freshwater: 12,46 mg/kg
PNEC sediment, marine water: 12,46 mg/kg
PNEC, soil: 2,31 mg/kg
PNEC sewage treatment plant (STP): 6,58 mg/L

Barium sulfate

EC No. 231-784-4 / CAS No. 7727-43-7

PNEC aquatic, freshwater: 0,115 mg/L
PNEC sediment, freshwater: 600,4 mg/kg
PNEC, soil: 207,7 mg/kg
PNEC sewage treatment plant (STP): 62,2 mg/L

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7

PNEC aquatic, freshwater: 0,184 mg/L
PNEC aquatic, marine water: 0,0184 mg/L
PNEC aquatic, intermittent release: 0,193 mg/L
PNEC sediment, freshwater: 1000 mg/kg
PNEC sediment, marine water: 100 mg/kg
PNEC, soil: 100 mg/kg
PNEC sewage treatment plant (STP): 100 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear-time limits as specified by the manufacturer. Recommended respiratory protection articles : Inadequately ventilated workplaces and spraying procedures are necessary. Fresh air mask or short-time work combination filter A2-P2 are recommended.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material $> 0,4 \text{ mm}$; Breakthrough time: $> 480 \text{ min}$.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state:

Liquid

Appearance:

Liquid

Colour:

refer to label

Odour:

characteristic

Odour threshold:

No data available

pH at 20 °C:

no information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 22-3 Ahrweitex- Schnellspachtel
Print date 09.02.2026 Revision date 28.08.2025
Version 25.7 Issue date 28.08.2025

EN
Page 6 / 11

Melting point/freezing point:	< -20 °C Source: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics
Initial boiling point and boiling range:	111 °C Source: Toluene
Flash point:	No data available
Evaporation rate:	No data available
flammability	
Burning time:	No data available
Upper/lower flammability or explosive limits:	
Lower explosion limit:	0,8 Vol-% Method: literature value
Upper explosion limit:	No data available
Vapour pressure at 20 °C:	14 mbar Source: Xylene
Vapour density:	No data available
Relative density:	
Density at 20 °C:	2,17 g/cm³ Method: DIN 53217
Solubility(ies):	
Water solubility at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity at °C:	paste-like
Explosive properties:	No data available
Oxidising properties:	No data available
9.2. Other information	
Solid content:	87 weight-%
solvent content:	
Organic solvents:	13 weight-%
Water:	0 weight-%

SECTION 10: Stability and reactivity

- 10.1. **Reactivity**
No information available.
- 10.2. **Chemical stability**
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.
- 10.3. **Possibility of hazardous reactions**
Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.
- 10.4. **Conditions to avoid**
Hazardous decomposition byproducts may form with exposure to high temperatures.
- 10.5. **Incompatible materials**
not applicable
- 10.6. **Hazardous decomposition products**
Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]
No data on preparation itself available.

- 11.1. **Information on toxicological effects**

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 22-3 Ahrweitex- Schnellspachtel
Print date 09.02.2026 Revision date 28.08.2025
Version 25.7 Issue date 28.08.2025

EN
Page 7 / 11

Acute toxicity

Linseed oil

oral, LD50, Rat: > 5000 mg/kg

Ethylbenzene

oral, LD50, Rat: 3500 mg/kg

dermal, LD50, Rabbit: 5000 mg/kg

inhalative (vapours), LC50, Rat: 17,2 mg/L (4 h)

Xylene

oral, LD50, Rat: 3523 mg/kg

dermal, LD50, Rabbit: 4200 mg/kg

inhalative (vapours), LC50, Rat: 10 - 20 mg/L (4 h)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 18,5 mg/L (4 h)

Talc (Mg₃H₂(SiO₃)₄)

oral, LD50, Rat: > 5000 mg/kg

Castor oil, hydrogenated

oral, LD50, Rat: > 5000 mg/kg

Barium sulfate

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 425

dermal, LD50, Rabbit: > 2000 mg/kg

inhalative (dust and mist), LC50, Rat: 3,43 - 5,09 mg/L (4 h)

Method: OECD 403

Skin corrosion/irritation; Serious eye damage/eye irritation

Xylene

Skin

Irritant — skin irritation and eye damage

eyes

mildly irritating

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Skin (4 h)

mild irritant.

eyes

mild irritant.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

Xylene

Specific target organ toxicity (single exposure), Irritation

Irritation to respiratory tract

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Specific target organ toxicity (single exposure), drowsiness

Narcotic effects

Aspiration hazard

Ethylbenzene

Aspiration hazard

Article No.: 22-3 Ahrweitex- Schnellspachtel
Print date 09.02.2026 Revision date 28.08.2025
Version 25.7 Issue date 28.08.2025

EN
Page 8 / 11

Xylene

Aspiration hazard

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Aspiration hazard

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

Linseed oil

Fish toxicity, LC50, Danio rerio (zebrafish): > 1000 mg/L (96 h)

Ethylbenzene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 4,2 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna 1,8 - 2,4 mg/L (48 h)

Algae toxicity, IC50:, Selenastrum capricornutum: 4,6 mg/L (72 h)

Xylene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 2,6 mg/L (96 h)

Method: OECD 203

Algae toxicity, EC50, Pseudokirchneriella subcapitata: 4,36 mg/L (73 h)

Method: OECD 201

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1 mg/L (24 h)

Method: OECD 202

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 1000 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna: > 1000 mg/L (48 h)

Method: OECD 202

Algae toxicity, EC50, Pseudokirchneriella subcapitata: > 1000 mg/L (72 h)

Method: OECD 201

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 100 mg/L (96 h)

Daphnia toxicity, LC50, Daphnia magna: > 100 mg/L (48 h)

Algae toxicity, EC50, Pseudokirchneriella subcapitata: 16 mg/L (72 h)

Long-term Ecotoxicity

Xylene

Fish toxicity, NOEC, Oncorhynchus mykiss (Rainbow trout): > 1,3 mg/L (56 d)

Daphnia toxicity, NOEC, Daphnia sp.: 0,96 mg/L (7 d)

Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 0,44 mg/L (72 h)

Method: OECD 201

Bacteria toxicity, NOEC, Activated sludge: 157 mg/L (3 h)

Method: OECD 209

12.2. Persistence and degradability

Ethylbenzene

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.:	22-3	Ahrweitex- Schnellspachtel	EN
Print date	09.02.2026	Revision date 28.08.2025	
Version	25.7	Issue date 28.08.2025	Page 9 / 11

Biodegradation: 100 % (6 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301E

Xylene

Biodegradation: 87,8 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Biodegradation: 80 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

Ethylbenzene

Partition coefficient: n-octanol/water: 3,2

Xylene

Partition coefficient: n-octanol/water: 2,77 - 3,15

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Partition coefficient n-octanol /water (log P O/W):: 5 - 6,7

Bioconcentration factor (BCF)

Ethylbenzene

Bioconcentration factor (BCF): 1

Xylene

Bioconcentration factor (BCF), Oncorhynchus mykiss (Rainbow trout): 25,9

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Bioconcentration factor (BCF): 10 - 2500

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Bioconcentration factor (BCF), Oncorhynchus mykiss (Rainbow trout): 19 - 352

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

14.1. UN number

No data available

14.2. UN proper shipping name

14.3. Transport hazard class(es)

No data available

14.4. Packing group

No data available

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 22-3 Ahrweitex- Schnellspachtel
Print date 09.02.2026 Revision date 28.08.2025
Version 25.7 Issue date 28.08.2025 EN
Page 10 / 11

14.5. Environmental hazards

Land transport (ADR/RID) No data available
Marine pollutant No data available

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code -

Sea transport (IMDG)

EmS-No. No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

This product is not classified according to Directive 2012/18/EU.

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
215-535-7 1330-20-7	Xylene	01-2119488216-32
919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics	01-2119463258-33
202-849-4 100-41-4	Ethylbenzene	01-2119489370-35

SECTION 16: Other information

Full text of classification in section 3:

Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.

Abbreviations and acronyms

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.:	22-3	Ahrweitex- Schnellspachtel	
Print date	09.02.2026	Revision date 28.08.2025	EN
Version	25.7	Issue date 28.08.2025	Page 11 / 11

OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MAK	Maximum workplace concentration
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Data sources

Data arise from reference works and literature.

Further information

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.