

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.:	16-20	Ultra-Primer	
Print date	09.02.2026	Revision date	24.11.2025
Version	1.101	Issue date	24.11.2025
			EN
			Page 1 / 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier):	16-20
Trade name/designation	Ultra-Primer
	weiß
	seidenmatt
	UFI: 151P-9JYS-3G0D-000J

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Primer

Uses advised against:

Aware of any other information

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

P.A. Jansen GmbH u. Co., KG	
Hochstadenstraße 22	Telephone: +49 2641 3897-0
D-53474 Bad Neuenahr-Ahrweiler	
	Homepage: www.jansen.de

Department responsible for information:

laboratory

E-mail (competent person) sicherheitsdatenblatt@jansen.de

1.4. Emergency telephone number

Emergency telephone number	+49 2641 3897-51
Only available during office hours.	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and eye protection/face protection.
P370 + P378.6	In case of fire: Use carbon dioxide, extinguishing powder or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard components for labelling

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20 Ultra-Primer
Print date 09.02.2026 Revision date 24.11.2025
Version 1.101 Issue date 24.11.2025

EN
Page 2 / 14

1,2,2,6,6-pentamethyl-4-piperidyl sebacate
Hydrocarbons, C9, aromatics

Supplemental hazard information

No data available

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description plastic ground

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
918-668-5	01-2119455851-35 Hydrocarbons, C9, aromatics Flam. Liq. 3 H226 / STOT SE 3 H335 / Aquatic Chronic 2 H411 / Asp. Tox. 1 H304 / STOT SE 3 H336 / EUH066	12,5 - 15
215-535-7 1330-20-7 601-022-00-9	01-2119488216-32 Xylene Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / STOT SE 3 H335 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Flam. Liq. 3 H226 Acute toxicity estimate (ATE): ATE (dermal): 4200 mg/kg bw	7 - 8
231-944-3 7779-90-0 030-011-00-6 918-481-9	01-2119485044-40 Trizinc bis(orthophosphate) Aquatic Acute 1 H400 (M = 1) / Aquatic Chronic 1 H410 (M = 1)	3 - 5
927-241-2	01-2119457273-39 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics Asp. Tox. 1 H304 / EUH066	3 - 5
202-849-4 100-41-4 601-023-00-4	01-2119471843-32 hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2 % aromatics STOT SE 3 H336 / Asp. Tox. 1 H304 / Aquatic Chronic 3 H412 / Flam. Liq. 3 H226 / EUH066	1,5 - 2
252-104-2 34590-94-8	01-2119489370-35 Ethylbenzene Acute Tox. 4 H332 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Aquatic Chronic 3 H412 / Flam. Liq. 2 H225 Acute toxicity estimate (ATE): ATE (inhalation, vapour): 17,20 mg/L	1 - 1,5
215-222-5 1314-13-2 030-013-00-7 262-309-9 60580-61-2	01-2119450011-60 (2-methoxymethylethoxy)propanol Substance with a common (EC) occupational exposure limit value.	1 - 1,5
915-687-0 1065336-91-5	01-2119463881-32 zinc oxide Aquatic Acute 1 H400 (M = 1) / Aquatic Chronic 1 H410 (M = 1)	0,3 - 0,5
	01-2120768444-47 Aquatic Acute 1 H400 (M = 1) / Aquatic Chronic 2 H411	0,3 - 0,5
	01-2119491304-40 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate Skin Sens. 1A H317 / Repr. 2 H361 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	0,1 - 0,15

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20 Ultra-Primer
Print date 09.02.2026 Revision date 24.11.2025
Version 1.101 Issue date 24.11.2025

EN
Page 3 / 14

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. **Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. **Advice for firefighters**

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. **Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. **Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. **Reference to other sections**

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. **Precautions for safe handling**

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20 Ultra-Primer
Print date 09.02.2026 Revision date 24.11.2025
Version 1.101 Issue date 24.11.2025

EN
Page 4 / 14

using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m³; 50 ppm

WEL, STEL: 441 mg/m³; 100 ppm

Remark: (may be absorbed through the skin)

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

EC No. 918-481-9

WEL, TWA: 800 mg/m³

Remark: (> or = C7, Cycloalkanes)

WEL, TWA: 1200 mg/m³

Remark: (alkanes >= C7)

Ethylbenzene

Index No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

WEL, TWA: 441 mg/m³; 100 ppm

WEL, STEL: 552 mg/m³; 125 ppm

Remark: (may be absorbed through the skin)

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

WEL, TWA: 308 mg/m³; 50 ppm

Remark: (may be absorbed through the skin)

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

Ethylbenzene

Index No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

DNEL long-term dermal (systemic), Workers: 180 mg/kg

DNEL long-term inhalative (local), Workers: 293 mg/m³

DNEL long-term inhalative (systemic), Workers: 77 mg/m³

DNEL long-term inhalative (local), Workers: 293 mg/m³

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20 Ultra-Primer
Print date 09.02.2026 Revision date 24.11.2025
Version 1.101 Issue date 24.11.2025

EN
Page 5 / 14

DNEL long-term oral (repeated), Consumer: 1,6 mg/kg
DNEL acute inhalative (systemic), Consumer: 15 mg/m³

zinc oxide

Index No. 030-013-00-7 / EC No. 215-222-5 / CAS No. 1314-13-2

DNEL long-term dermal (systemic), Workers: 83 mg/kg
DNEL long-term inhalative (local), Workers: 0,5 mg/m³
DNEL long-term inhalative (systemic), Workers: 5 mg/m³
DNEL long-term oral (repeated), Consumer: 0,83 mg/kg
DNEL long-term dermal (systemic), Consumer: 83 mg/kg
DNEL long-term inhalative (systemic), Consumer: 2,5 mg/m³

Trizinc bis(orthophosphate)

Index No. 030-011-00-6 / EC No. 231-944-3 / CAS No. 7779-90-0

DNEL long-term dermal (systemic), Workers: 83 mg/kg
DNEL long-term inhalative (systemic), Workers: 5 mg/m³
DNEL long-term oral (repeated), Consumer: 0,83 mg/kg
DNEL long-term dermal (systemic), Consumer: 83 mg/kg
DNEL long-term inhalative (systemic), Consumer: 2,5 mg/m³

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

DNEL long-term dermal (systemic), Workers: 212 mg/kg
DNEL acute inhalative (local), Workers: 442 mg/m³
DNEL acute inhalative (systemic), Workers: 442 mg/m³
DNEL long-term inhalative (local), Workers: 221 mg/m³
DNEL long-term inhalative (systemic), Workers: 221 mg/m³
DNEL long-term oral (repeated), Consumer: 12,5 mg/kg
DNEL long-term dermal (systemic), Consumer: 125 mg/kg
DNEL acute inhalative (local), Consumer: 260 mg/m³
DNEL acute inhalative (systemic), Consumer: 260 mg/m³
DNEL long-term inhalative (local), Consumer: 65,3 mg/m³
DNEL long-term inhalative (systemic), Consumer: 65,3 mg/m³

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

DNEL long-term dermal (systemic), Workers: 65 mg/kg
DNEL long-term inhalative (systemic), Workers: 310 mg/m³
DNEL long-term oral (repeated), Consumer: 1,67 mg/kg
DNEL long-term dermal (systemic), Consumer: 15 mg/kg
DNEL long-term inhalative (systemic), Consumer: 37,2 mg/m³

Hydrocarbons, C9, aromatics

EC No. 918-668-5

DNEL long-term dermal (systemic), Workers: 25 mg/kg
DNEL long-term inhalative (systemic), Workers: 150 mg/m³
DNEL long-term oral (repeated), Consumer: 11 mg/kg
DNEL long-term dermal (systemic), Consumer: 11 mg/kg
DNEL long-term inhalative (systemic), Consumer: 32 mg/m³

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

EC No. 918-481-9

DNEL long-term dermal (systemic), Workers: 300 mg/kg
DNEL long-term oral (repeated), Consumer: 300 mg/kg
DNEL long-term dermal (systemic), Consumer: 300 mg/kg
DNEL long-term inhalative (systemic), Consumer: 900 mg/m³

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

EC No. 927-241-2

DNEL long-term dermal (systemic), Workers: 300 mg/kg
DNEL long-term inhalative (systemic), Workers: 1500 mg/m³
DNEL long-term oral (repeated), Consumer: 300 mg/kg
DNEL long-term dermal (systemic), Consumer: 300 mg/kg
DNEL long-term inhalative (systemic), Consumer: 900 mg/m³

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20 Ultra-Primer
Print date 09.02.2026 Revision date 24.11.2025
Version 1.101 Issue date 24.11.2025

EN
Page 6 / 14

DNEL long-term inhalative (local), Workers: 10 mg/m³
DNEL long-term oral (repeated), Consumer: 700 mg/kg

PNEC:

Ethylbenzene

Index No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

PNEC aquatic, freshwater: 0,1 mg/L
PNEC aquatic, marine water: 0,01 mg/L
PNEC aquatic, intermittent release: 0,1 mg/L
PNEC sediment, freshwater: 13,7 mg/kg
PNEC sediment, marine water: 1,37 mg/kg
PNEC, soil: 2,68 mg/kg
PNEC sewage treatment plant (STP): 9,6 mg/L
PNEC Secondary Poisoning: 20 mg/kg

zinc oxide

Index No. 030-013-00-7 / EC No. 215-222-5 / CAS No. 1314-13-2

PNEC aquatic, freshwater: 0,0206 mg/L
PNEC aquatic, marine water: 0,0061 mg/L
PNEC sediment, freshwater: 117,8 mg/kg
PNEC sediment, marine water: 56,5 mg/kg
PNEC, soil: 35,6 mg/kg
PNEC sewage treatment plant (STP): 0,1 mg/L

Trizinc bis(orthophosphate)

Index No. 030-011-00-6 / EC No. 231-944-3 / CAS No. 7779-90-0

PNEC aquatic, freshwater: 20,6 µg/L
PNEC aquatic, marine water: 6,1 µg/L
PNEC sediment, freshwater: 117,8 mg/kg
PNEC sediment, marine water: 56,5 mg/kg
PNEC, soil: 35,6 mg/kg
PNEC sewage treatment plant (STP): 100 µg/L

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

PNEC aquatic, freshwater: 0,327 mg/L
PNEC aquatic, marine water: 0,327 mg/L
PNEC aquatic, intermittent release: 0,327 mg/L
PNEC sediment, freshwater: 12,46 mg/kg
PNEC sediment, marine water: 12,46 mg/kg
PNEC, soil: 2,31 mg/kg
PNEC sewage treatment plant (STP): 6,58 mg/L

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

PNEC aquatic, freshwater: 19 mg/L
PNEC aquatic, marine water: 1,9 mg/L
PNEC aquatic, intermittent release: 190 mg/L
PNEC sediment, freshwater: 70,2 mg/kg
PNEC sediment, marine water: 7,02 mg/kg
PNEC, soil: 2,74 mg/kg
PNEC sewage treatment plant (STP): 4168 mg/L

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7

PNEC aquatic, freshwater: 0,184 mg/L
PNEC aquatic, marine water: 0,0184 mg/L
PNEC aquatic, intermittent release: 0,193 mg/L
PNEC sediment, freshwater: 1000 mg/kg
PNEC sediment, marine water: 100 mg/kg
PNEC, soil: 100 mg/kg
PNEC sewage treatment plant (STP): 100 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Article No.: 16-20 Ultra-Primer
Print date 09.02.2026 Revision date 24.11.2025
Version 1.101 Issue date 24.11.2025

EN
Page 7 / 14

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits as specified by the manufacturer. Recommended respiratory protection articles: Inadequately ventilated workplaces and spraying procedures are necessary. Fresh air mask or short-time work combination filter A2-P2 are recommended.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	white
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	-84 °C Source: hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2 % aromatics
Initial boiling point and boiling range:	124 °C Source: Xylene
Flammability:	Flammable liquid and vapour.
Lower and upper explosion limit:	
Lower explosion limit:	0,7 Vol-% Method: literature value Source: Hydrocarbons, C9, aromatics
Upper explosion limit:	7 Vol-% Method: literature value Source: Hydrocarbons, C9, aromatics
Flash point:	36 °C Method: EN ISO 1523
Auto-ignition temperature:	400 °C Source: Hydrocarbons, C9, aromatics
Decomposition temperature:	No data available
pH at 20 °C:	No data available
Kinematic viscosity (40°C):	> 20,5 mm²/s
Viscosity at 23 °C:	> 90 s 4 mm Method: DIN 53211

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20 Ultra-Primer
Print date 09.02.2026 Revision date 24.11.2025
Version 1.101 Issue date 24.11.2025

EN
Page 8 / 14

Solubility(ies):
Water solubility at 20 °C: insoluble
Partition coefficient: n-octanol/water: see section 12
Vapour pressure at 20 °C: 14 mbar
Source: Xylene
Density and/or relative density:
Density at 20 °C: 1,46 g/cm³
Method: DIN 53217
Relative vapour density: No data available
particle characteristics: not applicable

9.2. **Other information**
Solid content: 73 weight-%
solvent content:
Organic solvents: 27 weight-%
Water: 0 weight-%

SECTION 10: Stability and reactivity

- 10.1. **Reactivity**
No information available.
- 10.2. **Chemical stability**
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.
- 10.3. **Possibility of hazardous reactions**
Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.
- 10.4. **Conditions to avoid**
Hazardous decomposition byproducts may form with exposure to high temperatures.
- 10.5. **Incompatible materials**
not applicable
- 10.6. **Hazardous decomposition products**
Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Ethylbenzene

oral, LD50, Rat: 3500 mg/kg
dermal, LD50, Rabbit: 5000 mg/kg
inhalative (vapours), LC50, Rat: 17,2 mg/L (4 h)

zinc oxide

oral, LD50, Rat: > 15000 mg/kg

Trizinc bis(orthophosphate)

oral, LD50, Rat: > 5000 mg/kg
inhalative (dust and mist), LC50, Rat: > 5,7 mg/L (4 h)

Xylene

oral, LD50, Rat: 3523 mg/kg
dermal, LD50, Rabbit: 4200 mg/kg
inhalative (vapours), LC50, Rat: 10 - 20 mg/L (4 h)

(2-methoxymethylethoxy)propanol

oral, LD50, Rat: > 4000 mg/kg
Method: OECD 401
dermal, LD50, Rabbit: > 5000 mg/kg
inhalative (vapours), LC50, Rat: > 275 mg/kg (7 h)

Hydrocarbons, C9, aromatics

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20 Ultra-Primer
Print date 09.02.2026 Revision date 24.11.2025
Version 1.101 Issue date 24.11.2025

EN
Page 9 / 14

oral, LD50, Rat 2000 - 5000 mg/kg
Method: OECD 401
dermal, LD50, Rabbit: > 2000 mg/kg
Method: OECD 402
inhalative (vapours), LC50, Rat: > 10,2 mg/L (4 h)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics
oral, LD50, Rat: > 5000 mg/kg
Method: OECD 401
dermal, LD50, Rabbit: > 5000 mg/kg
Method: OECD 402
inhalative (vapours), LC50, Rat: > 4951 mg/L (4 h)
Method: OECD 403

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2 % aromatics
oral, LD50, Rat: > 5000 mg/kg
dermal, LD50, Rabbit: > 5000 mg/kg
inhalative (vapours), LC50, Rat: > 4951 mg/L (4 h)

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]
oral, LD50, Rat: > 5000 mg/kg
Method: OECD 425
dermal, LD50, Rabbit: > 2000 mg/kg
inhalative (dust and mist), LC50, Rat 3,43 - 5,09 mg/L (4 h)
Method: OECD 403

Skin corrosion/irritation; Serious eye damage/eye irritation

Xylene
Skin
Irritant — skin irritation and eye damage
eyes
mildly irritating
Hydrocarbons, C9, aromatics
eyes, Rabbit (24 h)
mild irritant.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

May cause respiratory irritation.

Xylene
Specific target organ toxicity (single exposure), Irritation
Irritation to respiratory tract
Hydrocarbons, C9, aromatics
Specific target organ toxicity (single exposure), Irritation
Irritation to respiratory tract
Specific target organ toxicity (single exposure), drowsiness
Narcotic effects

Aspiration hazard

Ethylbenzene
Aspiration hazard
Xylene
Aspiration hazard
Hydrocarbons, C9, aromatics
Aspiration hazard
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics
Aspiration hazard

Practical experience/human evidence

Article No.: 16-20 Ultra-Primer
Print date 09.02.2026 Revision date 24.11.2025
Version 1.101 Issue date 24.11.2025

EN
Page 10 / 14

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

Ethylbenzene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 4,2 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna 1,8 - 2,4 mg/L (48 h)

Algae toxicity, IC50:, Selenastrum capricornutum: 4,6 mg/L (72 h)

zinc oxide

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 0,169 mg/L (96 h)

Daphnia toxicity, EC50: 0,413 mg/L (48 h)

Algae toxicity, ErC50, Selenastrum capricornutum: 0,136 mg/L

Trizinc bis(orthophosphate)

Daphnia toxicity, EC50: 2,44 mg/L (48 h)

Algae toxicity, ErC50, Selenastrum capricornutum: 0,8 mg/L (72 h)

Xylene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 2,6 mg/L (96 h)

Method: OECD 203

Algae toxicity, EC50, Pseudokirchneriella subcapitata: 4,36 mg/L (73 h)

Method: OECD 201

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1 mg/L (24 h)

Method: OECD 202

(2-methoxymethylethoxy)propanol

Fish toxicity, LC50, Poecilia reticulata (Guppy): > 1000 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna: 1919 mg/L (48 h)

Algae toxicity, EC50, Selenastrum capricornutum: > 969 mg/L (72 h)

Hydrocarbons, C9, aromatics

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 9,2 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 3,2 mg/L (48 h)

Method: OECD 202

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 2,629 mg/L (72 h)

Method: OECD 201

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 1000 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna: > 1000 mg/L (48 h)

Method: OECD 202

Algae toxicity, EC50, Pseudokirchneriella subcapitata: > 1000 mg/L

Method: OECD 201

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Article No.:	16-20	Ultra-Primer	
Print date	09.02.2026	Revision date 24.11.2025	EN
Version	1.101	Issue date 24.11.2025	Page 11 / 14

Fish toxicity, NOELR, Oncorhynchus mykiss (Rainbow trout) 10 - 30 mg/L (96 h)
Daphnia toxicity, NOELR, Daphnia magna (Big water flea) 22 - 46 mg/L (48 h)
Algae toxicity, NOELR, Pseudokirchneriella subcapitata: > 1000 mg/L (72 h)
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]
Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 100 mg/L (96 h)
Daphnia toxicity, LC50, Daphnia magna: > 100 mg/L (48 h)
Algae toxicity, EC50, Pseudokirchneriella subcapitata: 16 mg/L (72 h)

Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

zinc oxide

Bacteria toxicity, NOEC, Activated sludge: 0,1 mg/L (4 h)

Xylene

Fish toxicity, NOEC, Oncorhynchus mykiss (Rainbow trout): > 1,3 mg/L (56 d)

Daphnia toxicity, NOEC, Daphnia sp.: 0,96 mg/L (7 d)

Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 0,44 mg/L (72 h)

Method: OECD 201

Bacteria toxicity, NOEC, Activated sludge: 157 mg/L (3 h)

Method: OECD 209

(2-methoxymethylethoxy)propanol

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): > 0,5 mg/L (22 d)

Method: OECD 211

12.2. Persistence and degradability

Ethylbenzene

Biodegradation: 100 % (6 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301E

Xylene

Biodegradation: 87,8 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

(2-methoxymethylethoxy)propanol

Biodegradation, aerobic: Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

Hydrocarbons, C9, aromatics

Biodegradation, Degree of elimination:: 89 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Biodegradation: 80 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Biodegradation, Degree of elimination:: 89 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

Ethylbenzene

Partition coefficient: n-octanol/water: 3,2

Xylene

Partition coefficient: n-octanol/water: 2,77 - 3,15

(2-methoxymethylethoxy)propanol

Partition coefficient n-octanol /water (log P O/W):: 0,004

Method: OECD 107

Hydrocarbons, C9, aromatics

Partition coefficient n-octanol /water (log P O/W):: 3,7 - 4,5

Bioconcentration factor (BCF)

Ethylbenzene

Bioconcentration factor (BCF): 1

Xylene

Bioconcentration factor (BCF), Oncorhynchus mykiss (Rainbow trout): 25,9

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.:	16-20	Ultra-Primer	
Print date	09.02.2026	Revision date	24.11.2025
Version	1.101	Issue date	24.11.2025
		EN	
		Page 12 / 14	

Bioconcentration factor (BCF), Oncorhynchus mykiss (Rainbow trout): 19 - 352

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1263

14.2. UN proper shipping name

Land transport (ADR/RID):

Paint

Sea transport (IMDG):

PAINT

Air transport (ICAO-TI / IATA-DGR):

Paint

14.3. Transport hazard class(es)

3

14.4. Packing group

III

14.5. Environmental hazards

Land transport (ADR/RID)

UMWELTGEFÄHRDEND

Marine pollutant

p

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code

D/E

in packages <= 5 litres

Not goods of class 3

Sea transport (IMDG)

EmS-No.

F-E, S-E

in packages <= 5 litres

Transport in accordance with 2.3.2.5 of the IMDG Code.

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20
Print date 09.02.2026
Version 1.101

Ultra-Primer
Revision date 24.11.2025
Issue date 24.11.2025

EN
Page 13 / 14

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Category: P5c FLAMMABLE LIQUIDS

Quantity 1: 5000 t / Quantity 2: 50000 t

Category: E2 Hazardous to the aquatic environment in Category Chronic 2

Quantity 1: 200 t / Quantity 2: 500 t

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/i) ; VOC limit value: 500 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 500

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
918-668-5	Hydrocarbons, C9, aromatics	01-2119455851-35
215-535-7	Xylene	01-2119488216-32
1330-20-7		
231-944-3	Trizinc bis(orthophosphate)	01-2119485044-40
7779-90-0		
918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics	01-2119457273-39
927-241-2	hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2 % aromatics	01-2119471843-32
202-849-4	Ethylbenzene	01-2119489370-35
100-41-4		
252-104-2	(2-methoxymethylethoxy)propanol	01-2119450011-60
34590-94-8		
215-222-5	zinc oxide	01-2119463881-32
1314-13-2		
262-309-9		01-2120768444-47
60580-61-2		
915-687-0	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	01-2119491304-40
1065336-91-5	and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	

SECTION 16: Other information

*

Full text of classification in section 3:

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting effects.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20
Print date 09.02.2026
Version 1.101

Ultra-Primer
Revision date 24.11.2025
Issue date 24.11.2025

EN
Page 14 / 14

Skin Sens. 1A / H317
Repr. 2 / H361

Respiratory or skin sensitisation
Reproductive toxicity

May cause an allergic skin reaction.
Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 Flammable liquids On basis of test data.

Skin Sens. 1 Respiratory or skin sensitisation Calculation method.

STOT SE 3 STOT-single exposure Calculation method.

Aquatic Chronic 2 Hazardous to the aquatic environment Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MAK	Maximum workplace concentration
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Data sources

Data arise from reference works and literature.

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version