

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20-S Ultra-Primer Spray
Print date: 09.02.2026 Revision date: 13.10.2025 EN
Version: 1.39 Issue date: 13.10.2025 Page 1 / 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier): 16-20-S
Trade name/designation Ultra-Primer Spray
weiß
seidenmatt
UFI: QSYN-6JXE-6G0F-EHPH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Varnish / paint

Uses advised against:

Aware of any other information

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

P.A. Jansen GmbH u. Co., KG
Hochstadenstraße 22 Telephone: +49 2641 3897-0
D-53474 Bad Neuenahr-Ahrweiler
Homepage: www.jansen.de

Department responsible for information:

laboratory
E-mail (competent person) sicherheitsdatenblatt@jansen.de

1.4. Emergency telephone number

Emergency telephone number +49 2641 3897-51
Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Aerosol 1 / H222	Aerosol	Extremely flammable aerosol.
Aerosol 1 / H229	Aerosol	Pressurised container: May burst if heated.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P264 Wash hands thoroughly after handling.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20-S Ultra-Primer Spray
Print date: 09.02.2026 Revision date: 13.10.2025
Version: 1.39 Issue date: 13.10.2025

EN
Page 2 / 14

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves and eye protection/face protection.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard components for labelling

Acetone

Supplemental hazard information

EUH018 In use may form flammable/explosive vapour-air mixture.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

2.3. Other hazards

Do not use in confined spaces. Only use the product for the intended purpose.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description plastic ground

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
200-662-2 67-64-1 606-001-00-8	01-2119471330-49 Acetone Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066	25 - 35
200-827-9 74-98-6 601-003-00-5	01-2119486944-21 propane Flam. Gas 1 H220 / Compressed gas H280 / EUH018	15 - 20
203-448-7 106-97-8 601-004-00-0	01-2119474691-32 butane Flam. Gas 1 H220 / Compressed gas H280 / EUH018	8 - 10
918-668-5	01-2119455851-35 Hydrocarbons, C9, aromatics Flam. Liq. 3 H226 / STOT SE 3 H335 / Aquatic Chronic 2 H411 / Asp. Tox. 1 H304 / STOT SE 3 H336 / EUH066	5 - 7
215-535-7 1330-20-7 601-022-00-9	01-2119488216-32 Xylene Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / STOT SE 3 H335 / STOT RE 2 H373 / Asp. Tox. 1 H304 / Flam. Liq. 3 H226 Acute toxicity estimate (ATE): ATE (dermal): 4200 mg/kg bw	3 - 5
231-944-3 7779-90-0 030-011-00-6	01-2119485044-40 Trizinc bis(orthophosphate) Aquatic Acute 1 H400 (M = 1) / Aquatic Chronic 1 H410 (M = 1)	1,5 - 2
203-603-9 108-65-6 607-195-00-7	01-2119475791-29 2-methoxy-1-methylethyl acetate STOT SE 3 H336 / Flam. Liq. 3 H226	1,5 - 2
918-481-9	01-2119457273-39 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics Asp. Tox. 1 H304 / EUH066	1 - 1,5
215-222-5 1314-13-2 030-013-00-7	01-2119463881-32 zinc oxide Aquatic Acute 1 H400 (M = 1) / Aquatic Chronic 1 H410 (M = 1)	0,15 - 0,2
262-309-9 60580-61-2	01-2120768444-47 Aquatic Acute 1 H400 (M = 1) / Aquatic Chronic 2 H411	0,1 - 0,15

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.:	16-20-S	Ultra-Primer Spray	
Print date:	09.02.2026	Revision date: 13.10.2025	EN
Version:	1.39	Issue date: 13.10.2025	Page 3 / 14

915-687-0	01-2119491304-40	
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	0,036 - 0,05
	Skin Sens. 1A H317 / Repr. 2 H361 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

Article No.: 16-20-S Ultra-Primer Spray
Print date: 09.02.2026 Revision date: 13.10.2025
Version: 1.39 Issue date: 13.10.2025

EN
Page 4 / 14

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Protect from heat and direct sunlight. Ensure good ventilation / exhaustion at the workplace. Observe the exposure limits. Use only in well-ventilated areas. Ensure good interior ventilation, especially at floor level (vapors are heavier than air).

Further information

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Container under pressure. Protect from direct exposure to sunlight and temperatures exceeding 50 °C. Do not open with force, even when empty.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Protect from heat and direct sunlight. Take care of instructions on label.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

Acetone

Index No. 606-001-00-8 / EC No. 200-662-2 / CAS No. 67-64-1

WEL, TWA: 1210 mg/m³; 500 ppm

WEL, STEL: 3620 mg/m³; 1500 ppm

butane

Index No. 601-004-00-0 / EC No. 203-448-7 / CAS No. 106-97-8

WEL, TWA: 1450 mg/m³; 600 ppm

WEL, STEL: 1810 mg/m³; 750 ppm

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m³; 50 ppm

WEL, STEL: 441 mg/m³; 100 ppm

Remark: (may be absorbed through the skin)

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

2-methoxy-1-methylethyl acetate

Index No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

WEL, TWA: 274 mg/m³; 50 ppm

WEL, STEL: 548 mg/m³; 100 ppm

Remark: (may be absorbed through the skin)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

EC No. 918-481-9

WEL, TWA: 800 mg/m³

Remark: (> or = C7, Cycloalkanes)

WEL, TWA: 1200 mg/m³

Remark: (alkanes >= C7)

Additional information

TWA : Long-term occupational exposure limit value

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20-S Ultra-Primer Spray
Print date: 09.02.2026 Revision date: 13.10.2025
Version: 1.39 Issue date: 13.10.2025

EN
Page 5 / 14

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

Acetone

Index No. 606-001-00-8 / EC No. 200-662-2 / CAS No. 67-64-1

DNEL long-term dermal (systemic), Workers: 186 mg/kg

DNEL acute inhalative (local), Workers: 2420 mg/m³

DNEL acute inhalative (systemic), Workers: 1210 mg/m³

DNEL long-term inhalative (systemic), Workers: 1210 mg/m³

DNEL long-term oral (repeated), Consumer: 62 mg/kg

DNEL long-term dermal (systemic), Consumer: 62 mg/kg

DNEL long-term inhalative (systemic), Consumer: 200 mg/m³

2-methoxy-1-methylethyl acetate

Index No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

DNEL acute dermal, short-term (systemic), Workers: 153,5 mg/kg

DNEL long-term dermal (systemic), Workers: 796 mg/kg

DNEL acute inhalative (local), Workers: 550 mg/m³

DNEL long-term inhalative (systemic), Workers: 275 mg/m³

DNEL long-term oral (repeated), Consumer: 36 mg/kg

DNEL long-term dermal (systemic), Consumer: 320 mg/kg

DNEL acute inhalative (systemic), Consumer: 33 mg/m³

DNEL long-term inhalative (systemic), Consumer: 33 mg/m³

zinc oxide

Index No. 030-013-00-7 / EC No. 215-222-5 / CAS No. 1314-13-2

DNEL long-term dermal (systemic), Workers: 83 mg/kg

DNEL long-term inhalative (local), Workers: 0,5 mg/m³

DNEL long-term inhalative (systemic), Workers: 5 mg/m³

DNEL long-term oral (repeated), Consumer: 0,83 mg/kg

DNEL long-term dermal (systemic), Consumer: 83 mg/kg

DNEL long-term inhalative (systemic), Consumer: 2,5 mg/m³

Trizinc bis(orthophosphate)

Index No. 030-011-00-6 / EC No. 231-944-3 / CAS No. 7779-90-0

DNEL long-term dermal (systemic), Workers: 83 mg/kg

DNEL long-term inhalative (systemic), Workers: 5 mg/m³

DNEL long-term oral (repeated), Consumer: 0,83 mg/kg

DNEL long-term dermal (systemic), Consumer: 83 mg/kg

DNEL long-term inhalative (systemic), Consumer: 2,5 mg/m³

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

DNEL long-term dermal (systemic), Workers: 212 mg/kg

DNEL acute inhalative (local), Workers: 442 mg/m³

DNEL acute inhalative (systemic), Workers: 442 mg/m³

DNEL long-term inhalative (local), Workers: 221 mg/m³

DNEL long-term inhalative (systemic), Workers: 221 mg/m³

DNEL long-term oral (repeated), Consumer: 12,5 mg/kg

DNEL long-term dermal (systemic), Consumer: 125 mg/kg

DNEL acute inhalative (local), Consumer: 260 mg/m³

DNEL acute inhalative (systemic), Consumer: 260 mg/m³

DNEL long-term inhalative (local), Consumer: 65,3 mg/m³

DNEL long-term inhalative (systemic), Consumer: 65,3 mg/m³

Hydrocarbons, C9, aromatics

EC No. 918-668-5

DNEL long-term dermal (systemic), Workers: 25 mg/kg

DNEL long-term inhalative (systemic), Workers: 150 mg/m³

DNEL long-term oral (repeated), Consumer: 11 mg/kg

DNEL long-term dermal (systemic), Consumer: 11 mg/kg

DNEL long-term inhalative (systemic), Consumer: 32 mg/m³

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

EC No. 918-481-9

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20-S Ultra-Primer Spray
Print date: 09.02.2026 Revision date: 13.10.2025
Version: 1.39 Issue date: 13.10.2025

EN
Page 6 / 14

DNEL long-term dermal (systemic), Workers: 300 mg/kg
DNEL long-term oral (repeated), Consumer: 300 mg/kg
DNEL long-term dermal (systemic), Consumer: 300 mg/kg
DNEL long-term inhalative (systemic), Consumer: 900 mg/m³
titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]
Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7
DNEL long-term inhalative (local), Workers: 10 mg/m³
DNEL long-term oral (repeated), Consumer: 700 mg/kg

PNEC:

Acetone

Index No. 606-001-00-8 / EC No. 200-662-2 / CAS No. 67-64-1
PNEC aquatic, freshwater: 10,6 mg/L
PNEC aquatic, marine water: 1,06 mg/L
PNEC aquatic, intermittent release: 21 mg/L
PNEC sediment, freshwater: 30,4 mg/kg
PNEC sediment, marine water: 3,04 mg/kg
PNEC, soil: 29,5 mg/kg
PNEC sewage treatment plant (STP): 100 mg/L

2-methoxy-1-methylethyl acetate

Index No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6
PNEC aquatic, freshwater: 0,635 mg/L
PNEC aquatic, marine water: 0,0635 mg/L
PNEC aquatic, intermittent release: 6,35 mg/L
PNEC sediment, freshwater: 3,29 mg/kg
PNEC sediment, marine water: 0,329 mg/kg
PNEC, soil: 0,29 mg/kg
PNEC sewage treatment plant (STP): 100 mg/L

zinc oxide

Index No. 030-013-00-7 / EC No. 215-222-5 / CAS No. 1314-13-2
PNEC aquatic, freshwater: 0,0206 mg/L
PNEC aquatic, marine water: 0,0061 mg/L
PNEC sediment, freshwater: 117,8 mg/kg
PNEC sediment, marine water: 56,5 mg/kg
PNEC, soil: 35,6 mg/kg
PNEC sewage treatment plant (STP): 0,1 mg/L

Trizinc bis(orthophosphate)

Index No. 030-011-00-6 / EC No. 231-944-3 / CAS No. 7779-90-0
PNEC aquatic, freshwater: 20,6 µg/L
PNEC aquatic, marine water: 6,1 µg/L
PNEC sediment, freshwater: 117,8 mg/kg
PNEC sediment, marine water: 56,5 mg/kg
PNEC, soil: 35,6 mg/kg
PNEC sewage treatment plant (STP): 100 µg/L

Xylene

Index No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7
PNEC aquatic, freshwater: 0,327 mg/L
PNEC aquatic, marine water: 0,327 mg/L
PNEC aquatic, intermittent release: 0,327 mg/L
PNEC sediment, freshwater: 12,46 mg/kg
PNEC sediment, marine water: 12,46 mg/kg
PNEC, soil: 2,31 mg/kg
PNEC sewage treatment plant (STP): 6,58 mg/L

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]
Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7
PNEC aquatic, freshwater: 0,184 mg/L
PNEC aquatic, marine water: 0,0184 mg/L
PNEC aquatic, intermittent release: 0,193 mg/L
PNEC sediment, freshwater: 1000 mg/kg
PNEC sediment, marine water: 100 mg/kg

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20-S Ultra-Primer Spray
Print date: 09.02.2026 Revision date: 13.10.2025
Version: 1.39 Issue date: 13.10.2025

EN
Page 7 / 14

PNEC, soil: 100 mg/kg
PNEC sewage treatment plant (STP): 100 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits as specified by the manufacturer. Recommended respiratory protection articles: Inadequately ventilated workplaces and spraying procedures are necessary. Fresh air mask or short-time work combination filter A2-P2 are recommended.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	white
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	-95 °C Source: Acetone
Initial boiling point and boiling range:	-42 °C Source: propane
Flammability:	Extremely flammable aerosol.
Lower and upper explosion limit:	
Lower explosion limit:	1,4 Vol-% Method: literature value Source: butane
Upper explosion limit:	14,3 Vol-% Method: literature value Source: Acetone
Flash point:	-42 °C Method: EN ISO 1523
Ignition temperature in °C:	365 °C Source: butane
Decomposition temperature:	No data available
pH at 20 °C:	No data available
Viscosity at °C:	nicht bestimmt

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20-S Ultra-Primer Spray
Print date: 09.02.2026 Revision date: 13.10.2025
Version: 1.39 Issue date: 13.10.2025

EN
Page 8 / 14

Solubility(ies):
Water solubility at 20 °C: partially soluble
Partition coefficient: n-octanol/water: see section 12
Vapour pressure at 20 °C: 8327 mbar
Source: propane
Density and/or relative density:
Density at 20 °C: No data available
Relative vapour density: No data available
particle characteristics: not applicable

9.2. **Other information**

SECTION 10: Stability and reactivity

10.1. **Reactivity**

No information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

not applicable

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. **Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute toxicity

Acetone

oral, LD50, Rat: 5800 mg/kg

Method: OECD 401

dermal, LD50, Rat: > 15800 mg/kg

inhalative (vapours), LC50, Rat: 76 mg/L (4 h)

2-methoxy-1-methylethyl acetate

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 5000 mg/kg

inhalative (vapours), LC50, Rat: 35,7 mg/L (4 h)

zinc oxide

oral, LD50, Rat: > 15000 mg/kg

Trizinc bis(orthophosphate)

oral, LD50, Rat: > 5000 mg/kg

inhalative (dust and mist), LC50, Rat: > 5,7 mg/L (4 h)

Xylene

oral, LD50, Rat: 3523 mg/kg

dermal, LD50, Rabbit: 4200 mg/kg

inhalative (vapours), LC50, Rat: 10 - 20 mg/L (4 h)

Hydrocarbons, C9, aromatics

oral, LD50, Rat: 2000 - 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 2000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 10,2 mg/L (4 h)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20-S Ultra-Primer Spray
Print date: 09.02.2026 Revision date: 13.10.2025
Version: 1.39 Issue date: 13.10.2025

EN
Page 9 / 14

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 4951 mg/L (4 h)

Method: OECD 403

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 425

dermal, LD50, Rabbit: > 2000 mg/kg

inhalative (dust and mist), LC50, Rat 3,43 - 5,09 mg/L (4 h)

Method: OECD 403

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes serious eye irritation.

Acetone

Skin (4 h)

eyes, Rabbit.

Method: OECD 405

Irritating to eyes.

Xylene

Skin

Irritant — skin irritation and eye damage

eyes

mildly irritating

Hydrocarbons, C9, aromatics

eyes, Rabbit (24 h)

mild irritant.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

May cause drowsiness or dizziness.

Acetone

Specific target organ toxicity (single exposure), drowsiness

2-methoxy-1-methylethyl acetate

Specific target organ toxicity (single exposure), drowsiness

Xylene

Specific target organ toxicity (single exposure), Irritation

Irritation to respiratory tract

Hydrocarbons, C9, aromatics

Specific target organ toxicity (single exposure), Irritation

Irritation to respiratory tract

Specific target organ toxicity (single exposure), drowsiness

Narcotic effects

Aspiration hazard

Xylene

Aspiration hazard

Hydrocarbons, C9, aromatics

Aspiration hazard

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Aspiration hazard

Practical experience/human evidence

Article No.: 16-20-S Ultra-Primer Spray
Print date: 09.02.2026 Revision date: 13.10.2025
Version: 1.39 Issue date: 13.10.2025

EN
Page 10 / 14

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

Acetone

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 5540 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 100 mg/L (48 h)

Algae toxicity, ErC50, Selenastrum capricornutum: 7500 mg/L (96 h)

2-methoxy-1-methylethyl acetate

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 100 mg/L (96 h)

Method: OECD 201

Daphnia toxicity, EC50, Daphnia magna: 408 mg/L (48 h)

Bacteria toxicity, EC20:, Activated sludge: > 1000 mg/L (1 h)

Method: OECD 209

Algae toxicity, EC50, Pseudokirchneriella subcapitata: > 1000 mg/L (96 h)

Method: OECD 201

zinc oxide

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 0,169 mg/L (96 h)

Daphnia toxicity, EC50: 0,413 mg/L (48 h)

Algae toxicity, ErC50, Selenastrum capricornutum: 0,136 mg/L

Trizinc bis(orthophosphate)

Daphnia toxicity, EC50: 2,44 mg/L (48 h)

Algae toxicity, ErC50, Selenastrum capricornutum: 0,8 mg/L (72 h)

Xylene

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 2,6 mg/L (96 h)

Method: OECD 203

Algae toxicity, EC50, Pseudokirchneriella subcapitata: 4,36 mg/L (73 h)

Method: OECD 201

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1 mg/L (24 h)

Method: OECD 202

Hydrocarbons, C9, aromatics

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 9,2 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 3,2 mg/L (48 h)

Method: OECD 202

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 2,629 mg/L (72 h)

Method: OECD 201

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 1000 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna: > 1000 mg/L (48 h)

Method: OECD 202

Algae toxicity, EC50, Pseudokirchneriella subcapitata: > 1000 mg/L

Method: OECD 201

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.:	16-20-S	Ultra-Primer Spray	
Print date:	09.02.2026	Revision date: 13.10.2025	EN
Version:	1.39	Issue date: 13.10.2025	Page 11 / 14

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 100 mg/L (96 h)
Daphnia toxicity, LC50, Daphnia magna: > 100 mg/L (48 h)
Algae toxicity, EC50, Pseudokirchneriella subcapitata: 16 mg/L (72 h)

Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

Acetone

Daphnia toxicity, NOEC: 2212 mg/L (28 d)

2-methoxy-1-methylethyl acetate

Fish toxicity, NOEC, Oryzias latipes: 47,5 mg/L (14 d)

Daphnia toxicity, NOEC: > 100 mg/L (21 d)

Method: OECD 211

Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 1000 mg/L (72 h)

zinc oxide

Bacteria toxicity, NOEC, Activated sludge: 0,1 mg/L (4 h)

Xylene

Fish toxicity, NOEC, Oncorhynchus mykiss (Rainbow trout): > 1,3 mg/L (56 d)

Daphnia toxicity, NOEC, Daphnia sp.: 0,96 mg/L (7 d)

Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 0,44 mg/L (72 h)

Method: OECD 201

Bacteria toxicity, NOEC, Activated sludge: 157 mg/L (3 h)

Method: OECD 209

12.2. Persistence and degradability

Acetone

Biodegradation, Degree of elimination:: 91 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C

2-methoxy-1-methylethyl acetate

Biodegradation: 83 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

Xylene

Biodegradation: 87,8 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

Hydrocarbons, C9, aromatics

Biodegradation, Degree of elimination:: 89 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

Biodegradation: 80 % (28 d); Evaluation Readily biodegradable (according to OECD criteria)

Method: OECD 301F

12.3. Bioaccumulative potential

Acetone

Partition coefficient n-octanol /water (log P O/W):: -0,24

2-methoxy-1-methylethyl acetate

Partition coefficient n-octanol /water (log P O/W):: 1,2

Method: OECD 117

Xylene

Partition coefficient: n-octanol/water: 2,77 - 3,15

Hydrocarbons, C9, aromatics

Partition coefficient n-octanol /water (log P O/W):: 3,7 - 4,5

Bioconcentration factor (BCF)

Acetone

Bioconcentration factor (BCF): 3

Xylene

Bioconcentration factor (BCF), Oncorhynchus mykiss (Rainbow trout): 25,9

titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Bioconcentration factor (BCF), Oncorhynchus mykiss (Rainbow trout): 19 - 352

12.4. Mobility in soil

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20-S Ultra-Primer Spray
Print date: 09.02.2026 Revision date: 13.10.2025
Version: 1.39 Issue date: 13.10.2025

EN
Page 12 / 14

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

List of proposed waste codes/waste designations in accordance with EWC

160504* Gases in pressure containers (including halons) containing hazardous substances

150110* packaging containing residues of or contaminated by dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

Land transport (ADR/RID):

Aerosols, flammable

Sea transport (IMDG):

AEROSOLS

Air transport (ICAO-TI / IATA-DGR):

Aerosols, flammable

14.3. Transport hazard class(es)

2.1

14.4. Packing group

No data available

14.5. Environmental hazards

Land transport (ADR/RID)

UMWELTGEFÄHRDEND

Marine pollutant

p

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code

D

Sea transport (IMDG)

EmS-No.

F-D, S-U

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20-S Ultra-Primer Spray
Print date: 09.02.2026 Revision date: 13.10.2025
Version: 1.39 Issue date: 13.10.2025

EN
Page 13 / 14

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Category: P3a FLAMMABLE AEROSOLS

Quantity 1: 150 t / Quantity 2: 500 t

Category: E2 Hazardous to the aquatic environment in Category Chronic 2

Quantity 1: 200 t / Quantity 2: 500 t

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
200-662-2 67-64-1	Acetone	01-2119471330-49
200-827-9 74-98-6	propane	01-2119486944-21
203-448-7 106-97-8	butane	01-2119474691-32
918-668-5	Hydrocarbons, C9, aromatics	01-2119455851-35
215-535-7 1330-20-7	Xylene	01-2119488216-32
231-944-3 7779-90-0	Trizinc bis(orthophosphate)	01-2119485044-40
203-603-9 108-65-6	2-methoxy-1-methylethyl acetate	01-2119475791-29
918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics	01-2119457273-39
215-222-5 1314-13-2	zinc oxide	01-2119463881-32
262-309-9 60580-61-2		01-2120768444-47
915-687-0 1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	01-2119491304-40

SECTION 16: Other information

Full text of classification in section 3:

Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Flam. Gas 1 / H220	flammable gases	Extremely flammable gas.
Compressed gas / H280	Gases under pressure	Contains gas under pressure; may explode if heated.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting effects.
Skin Sens. 1A / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 16-20-S Ultra-Primer Spray
Print date: 09.02.2026 Revision date: 13.10.2025
Version: 1.39 Issue date: 13.10.2025

EN
Page 14 / 14

Repr. 2 / H361

Reproductive toxicity

Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Aerosol 1	Aerosol	On basis of test data.
Aerosol 1	Aerosol	On basis of test data.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.
Aquatic Chronic 2	Hazardous to the aquatic environment	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MAK	Maximum workplace concentration
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Data sources

Data arise from reference works and literature.

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version