

Additiv R

- Additive R -

General Description

Type of material:	Anti-slip agent
Applications:	Additive R may be used with various Jansen floor products to achieve slip resistance classes in acc. with DIN 51130. ▪ Aqua 2-component floor sealer (R11) ▪ ISO-TPL Stair and Parquet Lacquer (R11) ▪ Aqua Hall Marking MB (R10) ▪ 2K Aqua Hall Marking MB (R11) ▪ Surface Marking MB (R11) ▪ 2K Industrial Marking HB (R9)
Product properties:	To increase slip resistance. Additive R is always stirred into the final coating only. For full anti-slip performance, the application quantity of the last coating must be very meticulously calculated.
Packaging size:	500 g

Technical Data

Density:	ca. 2.5 g/cm ³
Viscosity:	powdery
Quantity to add:	10% (see: Important information on Page 2, or the Technical Data Sheets for the relevant products)

Method of Application

Substrate preparation:	Please in this respect heed the Technical Data Sheets for the individual products. The preparation of the substrate and painting must be scientifically and technically state of the art. Please also take note of the current BFS data sheets and the VOB (German Construction Contract Procedures), Part C, DIN 18363 Painting and Coating work.
------------------------	--

Coating structure:	For priming: Apply the same product as for the final coat in accordance with the Technical Data Sheet, without Additive R. Admix 10% Additive R for the final coat and stir well. Stir whilst working and after longer breaks.
Important information:	The application quantity of the final coating with admixed Additive R must be adhered to.
Coating methods:	Brushing, roller application
Storage:	Store in dry conditions
VOC value:	This product is not subject to VOC control.

Identification Marking:	Please take note of our updated Safety Data Sheet available on the Internet at www.jansen.de
--------------------------------	---

The technical information was compiled in accordance with the latest state of the art. An obligation for the general validity of the individual recommendations cannot, however, be accepted as the application and processing methods do not lie within our influence and the varying states of the substrates each require a decision as to the method of working suitable for workman and trade. The recommendations do not release the customer from the task of accepting responsibility for checking the products of the supplier company as to their suitability for the foreseen use. Applicable are the "General Terms and Conditions of Delivery and Payment in the Paint Industry" in the recommendation approved by the Federal Cartel Office (Bundeskartellamt) on 1. January 2018. On publication of this data sheet, all previous data sheets for this product become invalid.

UST-IdNr.: DE147923895