

Street Tattoo Primer

Outdoors

General description

Material type:	Resin mixture
Area of use:	For use exclusively as a primer for Jansen Street Tattoos.
Product features:	Ensures optimal adhesion of Jansen Street Tattoos to the surface.
Colour tone:	Colourless
Package sizes:	Spray: 750 ml Can: 5 kg

Technical data

Density at 20°C:	Spray: 0,879 - 0,881 Can: 0.901 g/cm ³
Consumption:	Spray: 300 ml/m ² Can: 300 g/m ²

Description of use

Type of application:	Spray: Spraying Can: Apply with a short pile roller for solvent-based products.
Substrate preparation:	The area to be marked must be completely dry, free of dust and separating substances (oil, grease, wax). If there is heavy soiling, e.g. moss, algae, etc., a high-pressure cleaner must be used (pre-cleaning one day before application). Reason: The surface needs sufficient time to dry, otherwise adhesion problems will arise. Old markings, chewing gum residue and other bonding difficulties must be removed mechanically. Do not apply if the surface temperature of the floor is above 40°C or below 5°C. Before applying a Jansen Street Tattoo, it is essential to follow the application instructions!

Application:**Spray:**

Shake the can thoroughly until you can hear the mixing ball moving.
– Shake for at least another 1–2 minutes. Spraying distance approx. 25 cm. Apply evenly to the pre-marked area.

Can:

For larger street tattoos (**approx. 5 m² or more**), use the liquid primer from the can.

The material is ready to apply.

Layer thickness: max. 120 µ

Tool: Lambskin roller

Flash-off time: at least 15 minutes at 23°C

Not reaching the airing time can lead to adhesion problems.

The drying time depends on the wet film thickness, temperature, humidity and the material and ceiling temperature. The approval to burn the Jansen Street Tattoos onto the surface coated with primer is given by the applier after checking that it is completely dry.

Storage:

Cool, dry and frost-free. Close opened containers tightly.

VOC value:

This product is not subject to any VOC category.

Labelling

Please refer to our current safety data sheet on the Internet at www.jansen.de

The technical information has been compiled in accordance with the current state of science and technology. However, the individual recommendations cannot be considered to be binding as application and processing methods are beyond our control and the different nature of the substrates requires working methods to be tailored accordingly from a professional and craftsmanship perspective. The recommendations do not release the customer from the obligation to test the supplier's products for their suitability for the intended use under their own responsibility. The "General Terms and Conditions of Delivery and Payment of the Paint Industry" in the recommendation approved by the Federal Cartel Office on 01 July 2018 shall apply. With the publication of this data sheet, all previous data sheets for this product lose their validity.

VAT no: DE147923895